

STATE OF NEW YORK

10844

IN ASSEMBLY

April 6, 2026

Introduced by M. of A. SANTABARBARA -- read once and referred to the
Committee on Housing

AN ACT to amend the real property law, in relation to the visitability
of new homes by persons with disabilities

The People of the State of New York, represented in Senate and Assem-
bly, do enact as follows:

1 Section 1. The real property law is amended by adding a new article
2 15-A to read as follows:

ARTICLE 15-A

VISITABILITY OF NEW CONSTRUCTION

Section 480. Purpose.

6 481. Applicability of new construction.

7 482. Visitability requirement.

8 483. Exclusion.

9 484. Enforcement.

10 § 480. Purpose. The purpose of this article is to establish minimum
11 regulations for the design and construction of new homes to provide
12 visitability to such homes by persons with disabilities.

13 § 481. Applicability of new construction. Any new dwelling unit which
14 was designed, constructed, or commissioned, contracted or otherwise
15 arranged for design or construction, by any person or entity who, at any
16 time during the commissioning design or construction, received New York
17 state or federal financial assistance for such design or construction
18 shall comply with the provisions of this article. State financial
19 assistance shall not include loans backed by the state of New York mort-
20 gage agency (SONYMA). Federal financial assistance shall not include
21 loans backed by federal national mortgage association (Fannie Mae) or
22 federal housing administration (FHA) financing or other mortgage loans
23 backed by a federal mortgage loan program. For purposes of this
24 section, the term "dwelling unit" shall mean a detached single family
25 home, a ground floor unit in a town house, or a ground floor unit in a
26 building of three or fewer dwelling units which is designed as, or
27 intended for occupancy as a residence.

EXPLANATION--Matter in italics (underscored) is new; matter in brackets
[-] is old law to be omitted.

LBD02488-02-6

1 § 482. Visitability requirement. The design and construction of a new
2 dwelling unit shall comply with the following requirements:

3 1. Accessible entrance. (a) Except as provided in paragraph (b) of
4 this subdivision, the ground level of such dwelling unit shall contain
5 at least one entrance to the dwelling unit that:

6 (i) is accessible to, and usable by, people with disabilities such
7 that all rooms on the level are connected by an accessible route;

8 (ii) does not contain any steps or any door threshold that exceeds
9 one-half inch in height; and

10 (iii) is located on a continuous unobstructed path from the public
11 street or driveway that serves the unit, which path at no point has a
12 slope exceeding one inch in rise for every twelve inches in length, has
13 a width of not less than thirty-six inches and has a cross slope not
14 greater than two percent of the width. Such unobstructed path shall be
15 able to be negotiated by a person and may include curb ramps, parking
16 access aisles, walks, and ramps.

17 (b) The provisions of paragraph (a) of this subdivision shall not
18 apply to a dwelling unit if:

19 (i) the finished grade of the site is too steep to provide a path
20 having a slope of one inch in rise for every twelve inches in length at
21 the front, side, or back of the unit;

22 (ii) there is no driveway serving the unit; and

23 (iii) there is no alley or other roadway capable of providing vehicu-
24 lar access to the rear or side of the unit.

25 2. Accessible interior doors. All doors that are designed to allow
26 passage within the ground level of such dwelling unit shall have an
27 unobstructed opening of at least thirty-six inches when the door is open
28 at a ninety-degree angle.

29 3. Accessible environmental controls. All environmental controls and
30 outlets located on the ground level of such dwelling unit shall be
31 located on the wall at least fifteen inches, but not more than forty-
32 eight inches, above the floor or, in the case of environmental controls
33 and outlets located directly above a counter, sink, or appliance, not
34 more than three inches above such counter, sink, or appliance.

35 4. Accessible habitable space and bathroom. The ground level of such
36 dwelling unit shall contain the following:

37 (a) At least one indoor room that has an area of not less than seventy
38 square feet and contains no side or dimension narrower than seven feet;
39 and

40 (b) At least one bathroom that contains, at a minimum, the following:

41 (i) clear floor space of thirty by forty-eight inches centered on and
42 contiguous to the sink, which is not encroached by the swing path of the
43 bathroom door;

44 (ii) a sink and a toilet that each allow for a parallel or head-on
45 approach by a person in a wheelchair; and

46 (iii) walls that are reinforced to be capable of supporting grab bars
47 that resist shear and bending forces of a minimum of two hundred fifty
48 pounds, as follows:

49 (A) All walls adjacent to the toilet shall have horizontal backing
50 reinforcements, each at least thirty-three inches, but not more than
51 thirty-six inches, above the floor, and sufficient to allow for a twenty-
52 four-inch grab bar on the wall behind the toilet and another forty-
53 two-inch grab bar on one or the other walls adjacent to the toilet.

54 (B) If a bathtub is present in the bathroom, such reinforcements shall
55 include:

1 (I) two backing reinforcements on the back wall of the bathtub, each
2 at least twenty-four inches long, at least twenty inches wide and not
3 more than twenty-four inches from the head end wall and not more than
4 twelve inches from the foot end wall, one in a horizontal position at
5 least thirty-three inches, but not more than thirty-six inches, above
6 the floor, and one nine inches above the rim of the bathtub;

7 (II) one backing reinforcement on the foot end wall of the bathtub, at
8 least twenty inches long, at least eighteen inches wide and located at
9 the front edge of the bathtub; and

10 (III) one backing reinforcement on the head end wall of the bathtub,
11 at least twelve inches long, at least eighteen inches wide and located
12 at the front edge of the bathtub.

13 (C) If a shower is present in the bathroom, such reinforcements shall
14 include backing reinforcements on at least two walls on which the
15 control valves are not located, each centered at least thirty-three
16 inches, but not more than thirty-six inches, above the floor and at
17 least eighteen inches wide.

18 § 483. Exclusion. This article shall not apply to sites whose physical
19 characteristics renders compliance with this article unreasonable.

20 § 484. Enforcement. Any person, firm, corporation, partnership or any
21 other business entity that violates any provision of this article shall
22 be subject to a civil penalty of not less than fifty nor more than five
23 hundred dollars for each such offense and each day on which such
24 violation occurs or continues to occur shall be a separate offense. Any
25 violation of this article shall be enforceable by the attorney general
26 and any aggrieved party, and any such party shall have the right to seek
27 legal and equitable relief and the court may award reasonable costs and
28 attorney's fees associated with such action.

29 § 2. This act shall take effect on the one hundred eightieth day after
30 it shall have become a law and shall apply to dwelling units the
31 construction of which begins on or after such date.